

# PURE TECHNOLOGY.



## COMPACT FILTRATION SYSTEM

---

## COOLANT MIST

---

## AC 3001 – AC 3002

---

- Can be mounted directly on the machine
- Continuously variable fan (0-10 V at 230 V version)
- Modular expansion up to 7,200 m<sup>3</sup>/h (4,238 cfm) (AC 3061/3062) is possible
- Low energy consumption through use of filter elements with no pressure loss and energy-efficient fans
- Single-stage or multiple-stage version for the separation of coolant mist
- Filter elements in the AC 3000 series are compatible with our AC 1000 & AC 8000 – AC 24000 filter series, which means low maintenance costs
- Electrostatic or mechanical
- Further versions: special design for magnesium applications
- Mobile design for multiple application areas
- Universal use for oil & emulsion mist
- High-voltage generator pre-programmed with two voltage levels (oil/emulsion)
- Service door opening available in left or right.
- Various options available
- Diverse range of accessories available
- CIP (Cleaning in Place) function optionally available
- Filtration efficiency > 99%

# PURE TECHNOLOGY.



## COMPACT FILTRATION SYSTEM

## COOLANT MIST

## AC 3001 – AC 3002

	AC 3001			AC 3001 SOLID			AC 3002 CIP		AC 3002		
	230 V	400 V	480 V*	230 V	400 V	480 V*	400 V	480 V*	230 V	400 V	480 V*
OIL MIST	✓	✓	✓				✓	✓	✓	✓	✓
EMULSION MIST	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
CIP							✓	✓			
FILTRATION PRINCIPLE	E	E	E	M	M	M	E	E	E	E	E
SUCTION CAPACITY	1,200 m <sup>3</sup> /h 706 cfm	1,200 m <sup>3</sup> /h 706 cfm	706 cfm	1,000 m <sup>3</sup> /h 589 cfm	1,000 m <sup>3</sup> /h 589 cfm	589 cfm	1,200 m <sup>3</sup> /h 706 cfm	706 cfm	1,200 m <sup>3</sup> /h 706 cfm	1,200 m <sup>3</sup> /h 706 cfm	706 cfm
FAN OUTPUT (FREE BLOWING)	2,400 m <sup>3</sup> /h 1,413 cfm	3,200 m <sup>3</sup> /h 1,883 cfm	1,883 cfm	2,400 m <sup>3</sup> /h 1,413 cfm	3,200 m <sup>3</sup> /h 1,883 cfm	1,883 cfm	2,400 m <sup>3</sup> /h 1,413 cfm	1,413 cfm	2,400 m <sup>3</sup> /h 1,413 cfm	3,200 m <sup>3</sup> /h 1,883 cfm	1,883 cfm
ELECTRICAL CONNECTION IN V, HZ, KVA	230, 50- 60, 0.78	400, 50, 1.23	480, 50, 1.23	230, 50- 60, 0.63	400, 50, 1.38	480, 50, 1.38	400, 50-60, 0.93	480, 50-60, 0.93	230, 50- 60, 0.93	400, 50, 1.38	480, 50, 1.38
DIFFERENTIAL PRESSURE IN PA	840	980	980	840	980	980	840	840	840	980	980
SOUND PRESSURE LEVEL IN dB(A) (APPROX.)	70	< 75	< 75	70	< 75	< 75	< 75	< 75	70	< 75	< 75
DIMENSIONS (LxWxH) MM	800 x 625 x 610	800 x 625 x 610		800 x 625 x 610	800 x 625 x 610		1,130 x 690 x 880		1,130 x 625 x 610	1,130 x 625 x 610	
DIMENSIONS (LxWxH) INCH	31 x 25 x 24	31 x 25 x 24	31 x 25 x 24	31 x 25 x 24	31 x 25 x 24	31 x 25 x 24	44 x 27 x 35	44 x 27 x 35	44 x 25 x 24	44 x 25 x 24	44 x 25 x 24
WEIGHT IN KG (APPROX.)	100	110		80	85		180		135	140	
WEIGHT IN LBS (APPROX.)	220	243	243	176	187	187	396	396	298	309	309

\* Switch cabinet according to UL 508 A  
E = electrostatical  
M = mechanical

LTA LUFTECHNIK GMBH

Junkerstraße 2  
77787 Nordrach  
Germany  
info@lta-filter.com  
+49 (0)7838 84 245

LTA INDUSTRIAL AIR  
CLEANING SYSTEMS S.R.O.

Lidická 66  
252 68 Středokluky  
Czech Republic  
info@lta-filter.com  
+420 233 012 113

LTA INDUSTRIAL AIR CLEANING  
SYSTEMS, INC.

2541 Technology Drive, #410  
Elgin, IL 60124  
USA  
info@lta-filter.com  
+1 847 488 0406

**JUNKER  
GROUP**

[WWW.LTA-FILTER.COM](http://WWW.LTA-FILTER.COM)