

PURE TECHNOLOGY.



LARGE FILTRATION SYSTEM

COOLANT MIST

AC 24000

- Single-stage or multiple-stage version for the separation of coolant mist
- Filter elements are compatible with our AC 1000 & AC 3000 filter series, which means low maintenance costs
- Low energy consumption due to air stream-optimized construction
- Universal use for oil & emulsion mist
- High-voltage generator pre-programmed with two voltage levels -> oil or emulsion
- Service door can be optionally opened toward the left or right
- Versatile options available
- Ability to filtrate larger areas or centralized locations.
- Optional CIP (Cleaning in Place) cleaning system
Function: the individual filter levels are cleaned via built-in nozzle holders with corresponding full-cone nozzles. This takes place without chemical additives or diluted solutions and offers the re-conditioning of cleaning oil using a cleaning centrifuge

PURE TECHNOLOGY.



LARGE FILTRATION SYSTEM

COOLANT MIST

AC 24000

FILTRATION SYSTEM	AC 24001	AC 24002	AC 24002 CIP
	230 Volt	230 Volt	230 Volt
OIL MIST	✓	✓	✓
EMULSION MIST	✓	✓	✓
ELECTROSTATIC	✓	✓	✓
VOLUME FLOW	24,000–26,000 m ³ /h 14,126–15,303 cfm	24,000–28,000 m ³ /h 14,126–16,480 cfm	24,000–28,000 m ³ /h 14,126–16,480 cfm
ELECTRICAL CONNECTION IN V, HZ, KVA	230, 50–60, 1.0	230, 50–60, 2.0	230, 50–60
DIFFERENTIAL PRESSURE IN PA	100	100	100
DIMENSIONS (LxWxH)	650x3,160x2,300 mm 25x124x91 Inch	1,010x3,160x2,300 mm 40x124x91 Inch	1,300x3,160x2,500 mm 51x124x98 Inch
WEIGHT (APPROX.)	1,100 kg 2,425 lbs	2,200 kg 4,850 lbs	2,400 kg 5,291 lbs

FAN	G 24024
FAN OUTPUT	24,000* m ³ /h 14,126 cfm
ELECTRICAL CONNECTION IN V, HZ, KVA	400, 48, 30
DIFFERENTIAL PRESSURE IN PA	1,500
SOUND PRESSURE LEVEL IN dB(A) (APPROX.)	79
DIMENSIONS (LxWxH)	2,222x2,400x2,280 mm 87x94x90 Inch
WEIGHT (APPROX.)	800 kg 1,763 lbs

* can be increased up to approx. 28,000 m³/h (16,480 cfm) using a frequency converter