

PURE TECHNOLOGY.



DUST FILTRATION SYSTEM

DUSTS

DF 60–200

- Manual or pneumatic cleaning is possible
- Collecting basin in various versions
- Various filter media available

- Can be used for simple industrial applications, where there is no compressed air supply available and/or transportable systems

	DF 60	DF 90	DF 140	DF 200
	400 V	400 V	400 V	400 V
DUST	✓	✓	✓	✓
POCKET	✓	✓	✓	✓
SUCTION CAPACITY	600 m ³ /h 353 cfm	900 m ³ /h 530 cfm	1,400 m ³ /h 824 cfm	2,000 m ³ /h 1,177 cfm
FAN OUTPUT IN (FREE BLOWING)	800 m ³ /h 471 cfm	1,100 m ³ /h 647 cfm	2,000 m ³ /h 1,177 cfm	2,600 m ³ /h 1,530 cfm
ELECTRICAL CONNECTION IN V, HZ, KVA	400–460, 50–60, 1.35	400–460, 50–60, 1.65	400–460, 50–60, 3.5	400–460, 50–60, 4.2
DIFFERENTIAL PRESSURE IN PA	1,050	1,200	1,600	1,800
SOUND PRESSURE LEVEL IN dB(A) (APPROX.)	70	72	74	75
DIMENSIONS (LxWxH)	650x550x1,205 mm 25x22x47 Inch	650x550x1,205 mm 25x22x47 Inch	850x750x2,395 mm 33x30x94 Inch	850x750x2,395 mm 33x30x94 Inch
WEIGHT (APPROX.)	88 kg 194 lbs	90 kg 198 lbs	175 kg 386 lbs	180 kg 397 lbs
COLLECTION BIN IN L	45	80	80	80